

SMARTUBE RS

THE FASTEST SMARTUBE

SELLING POINTS

ROLLING SPEED

LIGHTNESS

PROTECTION



DESCRIPTION

Smartube RS – Redefining Inner Tube Performance

Introducing the all-new **Smartube RS**: engineered to be up to **21% faster** than its predecessor, lighter, and featuring enhanced puncture protection. Thanks to a brand-new formulation, it sets a new standard—delivering unmatched performance, reliability, and versatility.

Whether you're using **Tube Type** or **Tubeless Ready (TLR)** tires, Smartube RS integrates seamlessly into your setup. Testing proves it offers rolling speeds comparable to sealant-based tubeless systems—without the mess or maintenance.

No compromises. No complications. Just pure speed, made simple.

Pair it with our **P ZERO Race RS** tires for the fastest, most efficient system we've ever created.



ROLLING RESISTANCE



LIGHTWEIGHT CONSTRUCTION



AIR RETENTION



HIGH PUNCTURE PROTECTION

DETAILS



Presta valve: mechanism with glued core, different lengths to work with the majority of rim depths, black colour to look clean and slick

For SmarTUBE RS:



DO NOT USE if bike is equipped with RIM Brakes.

DO NOT REPAIR replace if tube or valve is damaged.



POWER IS NOTHING WITHOUT CONTROL

TECH OVERVIEW

1 Material



NEW (TPU)
thermoplastic
polyurethane



Further development
of our TPU material,
now with even lower
hysteresis for lower
rolling resistance, at
the same weight and
compact volume.



UP TO 21%
FASTER THAN
SMARTUBE

| PRODUCT | SETTING | WEIGHT (g) | PUNCTURE PROTECTION THICKNESS (mm) |
|--------------------|------------------|------------|------------------------------------|
| Butyl | 25/32-622 | 125 | 16,7 |
| Latex | 30/38-622 | 80 | 29 |
| Smartube | 23/32-622 | 35 | 17 |
| Smartube RS | 26/35-622 | 32 | 22,5 |



LIGHTER AND
MORE PUNCTURE
PROTECTED

2 Comparison

| | REFERENCE | SETTING | TOTAL SYSTEM WEIGHT (g) | ROLLING RESISTANCE* | SMARTUBE RS is: |
|-----------|---------------------------------------|--------------------|-------------------------|---------------------|---|
| TUBE TYPE | PZERO RS Tubetype 28-622 (230g) | Butyl | 355 | 14.3 W | <ul style="list-style-type: none">• 24.3% faster than butyl• 12.2% faster than Smartube |
| | | Smartube | 266 | 13.1 W | |
| | | Smartube RS | 262 | 11.5 W | |
| TLR | PZERO RS TLR 28-622 (290g) | Sealant (40 ml) | 340 | 9.6 W | <ul style="list-style-type: none">• As fast as TLR, with less hassle• 21% faster than Smartube |
| | | Smartube | 326 | 12.4 W | |
| | | Smartube RS | 322 | 9.8 W | |

*Test conducted at usage pressure at 28 km/h

4 Range

| Product Name | Size | ETRTO | Valve type | IP CODE | Weight |
|----------------------------------|------------|-----------|-------------------|---------|--------|
| PZERO SmarTUBE RS 26/35-622 42mm | 700x26/35C | 26/35-622 | Presta 42mm Black | 4727900 | 32g |
| PZERO SmarTUBE RS 26/35-622 60mm | 700x26/35C | 26/35-622 | Presta 60mm Black | 4728100 | 33g |
| PZERO SmarTUBE RS 26/35-622 80mm | 700x26/35C | 26/35-622 | Presta 80mm Black | 4728000 | 34g |